

Initial Setup

The VBrick EthernetTV Set Top Box is shipped with Audio/Video, S-Video, and power cables, and a handheld IR remote control unit. (An optional wireless keyboard is also available from VBrick.)



Table 2. STB Front Panel – Left to Right

Infrared Sensor	Above LEDs. Used for IR remote control and wireless keyboard.
Waiting	Blinks red during initial start-up.
Transfer	Blinks white when accessing flash memory.
Power	Steady green when power is applied.
On/Off	On/Off push button.



Table 3. STB Rear Panel – Left to Right

Power Plug	Connects to power cord.
VGA Port	Used to view video on a VGA monitor.
Serial Port	Used for <u>Serial Port Passthrough</u> or to open a command line window.
PCI Card Slot	Not used.
S-Video	Connect to standard TV.
Video	Composite video out.
Audio Left/Right	Audio out left and right.
USB Ports (2)	Connect USB mouse and/or keyboard.
SPDIF	Digital audio. Not supported.
LAN1	Connect to local area network.
LAN2	Not used.
PS/2	Connect PS/2 keyboard or mouse.



Connecting to the Network

- ▼ To connect the set top box to a TV and the network using the cables provided:
1. Attach the set top box video-out to a TV using the left (yellow) connector or the S-Video connector.
 2. Connect the set-top box audio out (left and right) to a TV.
 3. Connect the set-top box to the network using the LAN1 port.
 4. Connect power cord to a power source.

